



DOI: **10.5958/2249-7137.2021.00782.5**

## THE MODELING OF OPTIMIZATION OF SUPERCRITICAL CO<sub>2</sub> EXTRACTION OF RESVERATROL FROM BERRIES OF MULBERRY

**Mukhammadiev Baxodir Temurovich\***; **Berdieva Zulfiya Muxiddinovna\*\***

<sup>1,2</sup>Bukhara Engineering Technological Institute,  
UZBEKISTAN

Email id: zulfiya.berdiyeva@inbox.ru

### ABSTRACT

*This study used a supercritical (SK) of CO<sub>2</sub> - extraction to extract resveratrol (RT) from the mulberry. To do this, define the conditions (preliminary experiments) of the extraction process, namely, the temperature, pressure and fluid flow SC (CO<sub>2</sub>). Given that this process is multifactorial, the method RSM - response surface methodology and CCRD - central composite rotatable design used to determine the optimum operating conditions of the process. The effectiveness of the established SC-CO<sub>2</sub> extraction conditions, expressed RT content in the extracts as compared with a yield of RT produced by the conventional extraction method, when applied SC-CO<sub>2</sub> modified polar co-solvent (ethanol). In describing the RT yield predictions using appropriately combined RSM with CCRD, we found that the yield of RT mainly depends on the pressure and quantity of SC-CO<sub>2</sub> used for extraction. It turned out that there is a significant relationship for the linear and quadratic terms of the relationship between the output of the RT and these parameters. Noticeable interaction between the three process parameters (pressure, SC-CO<sub>2</sub> temperature and flow rate) was observed. Mulberry is subjected to heat pre-treatment. Cooked thereafter pitch used as a raw material for the extraction of by SC-CO<sub>2</sub>. Initial studies for a wide spectrum of SC-CO<sub>2</sub> density value (690-780 kg / m<sup>3</sup>) indicates that it is possible to set optimum operating conditions for the RT isolation. According to RSM - analysis of the optimal process conditions: 15,8 MPa, 30,5<sup>0</sup> and 20,08 g CO<sub>2</sub> / g.d.m CO<sub>2</sub> consumption for the extraction of RT from licorice using SC-CO<sub>2</sub>. SC-CO<sub>2</sub> density calculated for the optimum pressure and temperature equal to 725 kg / m<sup>3</sup>, which was found as a result of a preliminary analysis of the correlation between the output of the RT and CO<sub>2</sub> density. The maximum yield of RT is equal to 0,052 g of 1 g of dried material (about 0,5% of extract) with SC-CO<sub>2</sub> density equal 725 kg/m<sup>3</sup>.*

*Preliminary tests performed at condition resulting in SC-CO<sub>2</sub> density ranging from 690 to 780 kg/m<sup>3</sup> indicated that at some pressure, temperature as well as consumption of supercritical fluids the optimal working conditions for resveratrol isolation could be determined. For this purpose the following range of working conditions of SK-CO<sub>2</sub> were tested by using Central Composite Rotatable Design (CCRD) and Response Surface Methodology (RSM): pressure from 18 to 30 MPa, temperature from 20<sup>0</sup> to 40<sup>0</sup> and consumption of SK-CO<sub>2</sub> from 12 to 24 g<sub>CO<sub>2</sub></sub>/g<sub>d.m.</sub>. The results of this investigation indicated that maximum yield RT 0,052 mg from 1 g materials on dry basis (about 0,5 % of total extract) at 15,8 MPa, 30,5<sup>0</sup> and 20,08 g<sub>CO<sub>2</sub></sub> /g<sub>d.m.</sub> could be obtained.*

**KEYWORDS:** Berries of mulberry, organic acids, glucose, fructose, essential oils, vitamins, carotenes, micro- and macro elements, resveratrol.

## REFERENCES

- [1] A. Bogdanovicht. Al. Supercritical carbon dioxide extraction of *Trigonellagoenum-graccum* L. Seed's: process optimization using response surface methodology. The jour. Super.Fluids.07.2016.P 44-50
- [2] Safarov AF, Gafurov KH The use of liquid carbon dioxide as a solvent for extracts from plants (review). Bukhara. 2014. P. 117.
- [3] Mukhammadieva Z.B., Berdieva Z.M. Food safety of CO<sub>2</sub>-extracts from plant raw materials // Universum: chemistry and biology. - 2020. - No. 4 (70) C 8-12.
- [4] S.M. Ghoreishiet. al. Response surface optimization of essential oil and diosgenin extraction from *Inbutisterrestis* via supercritical fluid technology. *Chem. Ing. Technol* 2012.35(1).P.133-141
- [5] B. Kaufmannet. al. Influence of plant extraction processes. *Phytohem.Anal.* 18.2007.P.70-76
- [6] P. Kraulis, P.R. Venskutionis. Optimization of supercritical carbon dioxide extraction of amaranth seeds by response surface methodology and characterization of extracts is plated from different plant cultivars. *Jour. Supercrit. Fluids.*2013. Vol.73 P.178
- [7] H. Matlab, Z. Sadat, A. Hezave. Training cascade-formed back propagation network modeling of spearmint oil extraction in a packed bea using SC-CO<sub>2</sub>. *Jour. Supercrit. Fluids.*2013. Vol.73.P.108
- [8] BerdievaZulfiaMuhiddinovnaFUNCTIONS AND FORMS OF CHEMICAL EXPERIMENT. 10.29013/ESR-20-1.2-48-50
- [9] Mukhammadiev BT, Gafurov K.H, MirzaevaSh.U., Supercritical [SC] -CO<sub>2</sub> extraction of glycyrrhizic acid from licorice roots, Kazan, Butlerov Communications, 2017. T.49. No. 1., C. - 108-113.

